

## **ACRYLINDO 1137-65**

Termosetting acrylic

### **Features**

- Good adhesion on aluminium
- Good adhesion on galvanized
- Gloss

ACRYLINDO 1137-65 is a thermoplastic acrylic resin which has good gloss, good hardness and good adhesion. It is designed for 1K direct to metal coating, suitable to aluminium and galvanized steel.

### **Typical Properties**

#### **Solvent composition:**

Xylene

n-butanol

NV (by wt, 150°C, 15 minutes)	%	65 ± 1
Viscosity (gadner, 25°C)		Z6 – Z8
Acid Value	mg KOH/g	27 - 40
Color (gadner)		Max 1
Appearance		Clear and Clean

### **Application**

Alumunium & Galvanized coating

General metal coating

### **Dilutability**

Aliphatic hydrocarbon	Not dilutable
Aromatic hydrocarbon	Dilutable
Ester	Dilutable
Ketone	Dilutable
Alcohol	Dilutable

### **Packing**

Resin is supplied in steel drum with net content 200 kgs.

### **Storage and Handling**

Stored in proper warehouse. Keep container closed when not in use. Storage life is 12 months after manufacture.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to us. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.