

SAFETY DATA SHEET**SEAMASTER 9400A EPOXY PRIMER****1. PRODUCT IDENTIFICATION**

Form Liquid
Colour Range of colours

2. HAZARDS IDENTIFICATION

Acute Health Hazards Prolonged and repeated exposure to the solvent vapors may affect the Central Nervous System.

Signs and Symptom of Over-exposure Headache, dizziness, nausea and loss of coordination are indication of excessive exposure to vapors or spray mists.

Chronic Health Hazards Prolonged over-exposure to solvent ingredients in section 3 may cause adverse affect to the liver, urinary and reproductive system.

3. INFORMATION ON INGREDIENT

CAS NO.	Hazardous Ingredient	Vapor Pressure (mm Hg)
1330-20-7	Xylene	5.9
71-36-3	Butanol	5.5
Propriet	Epoxy Polymer Part (I)	As Dust
Propriet	Polyamine adduct	As Dust
14807-96-6	Talc	As Dust
13463-67-7	Titanium Dioxide	As Dust

4. FIRST AID MEASURES

Inhalation Remove casualty to fresh air, keep warm and stay at rest. If breathing irregular or stopped, give artificial respiration and/or seek medical attention.

Skin Contaminated clothing should be removed. Wash with soap and water.

Eyes Rinse with plenty of clean water for 15 minutes. Keep eyes open. If irritation persists, seek medical attention.

Ingestion This is no hazard by this route in normal industrial use. If accidentally swallowed, may induce vomiting, keep warm and stay at rest and obtain medical aid.

In case of doubt, or if symptoms persist, obtain medical aid immediately.



SAFETY DATA SHEET**SEAMASTER 9400A EPOXY PRIMER****5. FIRE FIGHTING MEASURES**

Extinguishing Media	Water, mist, carbon dioxide, powder or foam. Do not use water jet which will spread fire.
Exposure Hazards	In case of fire, carbon dioxide and toxic fumes might be formed.
Protection Equipment	Wear self-contained breathing apparatus in confined spaces.
Fire Prevention	Flash Point about 28- 30°C - Flammable if expose to source of ignition during application and drying. Paint residues are liable to spontaneous combustion. Remove soiled clothes and masking etc. from the working area duly. Residues should be damped with water and stored in a closed metal container prior to disposal.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Ventilate area of spill Remove all persons not wearing suitable protective equipment.
Environmental Precautions	Must not be allowed to enter sewers or open bodies of water. Waste materials must be treated as a fire hazard and disposed of in accordance with the control of pollution regulations. Residues and drained cans of these products are not classed as special waste. Disposal according to local regulations.

7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes and respiratory tract. Ensure good ventilation or local exhaust. Keep away from sources of ignition. Take precautionary measures against static discharges.
Storage	Store tightly closed in a cool and well ventilated place. Keep away from sources of ignition.

8. PERSONAL PROTECTION

Working Environment		
Paint Cells	Open Air	Confined Space
Controlled Efficient Ventilation	Limited Natural Ventilation	Limited ventilation
Gloves of Nitrite Rubber	Gloves of Nitrite Rubber	Gloves of Nitrite Rubber Half Mask filter A



SAFETY DATA SHEET

SEAMASTER 9400A EPOXY PRIMER

9. PHYSICAL PROPERTIES

Density at 27 ± 2°C	1.45 ± 0.05 for white (Part I) 0.87 ± 0.05 (Part II)
Solid Content	68%
Viscosity at 27 ± 2°C	80 - 95ku
Vapor Density	>1
Flash Point	28 - 30°C

10. STABILITY AND REACTIVITY

Conditions to avoid	Sunlight & friction
Material to avoid	When in contact with oxidizing agents and strong acids will cause exothermic reactions.

11. TOXICOLOGICAL INFORMATION

Inhalation	Inhale high vapor concentration may cause headache, dizziness and drowsiness.
Skin	May cause irritation, prolonged and repeated exposure may cause dermatitis.
Eyes	Irritating
Ingestion	May cause headache, dizziness and nausea.

12. ECOLOGICAL INFORMATION

Waste from this product may present long term environmental hazard, thus landfill disposal must be considered less acceptable than incineration.

13. DISPOSAL CONSIDERATION

Disposal of in accordance with local and national regulations.



SAFETY DATA SHEET**SEAMASTER 9400A EPOXY PRIMER****14. TRANSPORTATION INFORMATION**

Category/MD	3.3
U.N. No.	1263
PSA Group	III
IMDG Class	3.3
Label	3
U.N. Code	1300

15. REGULATORY INFORMATION

Hazard Symbol

**Flammable****Irritant**

Risk Phrases	R10 R36/R36	Flammable Irritation to eyes and skin
Safety Phrases	S16 S29	Keep away from sources of ignition – No smoking Do not empty into drains

16. OTHER INFORMATION

The information and recommendation on this data sheet are based on our current data and believe to be correct, however; no guarantee or warrantee of any kind implied or expressed is made with respect to the information contained herein. Any use of this product, which is not in conformance with this data sheet, is the responsibility of the user.



Seamaster Paint (S) Pte Ltd
1 Soon Lee Street, #03-20 Pioneer Centre, Singapore 627605
Tel: (65) 62651118 Fax: 62687796
spsHQ@seamaster.com.sg
www.seamasterpaint.com